

Features

- 3 1/2 Digits (2000 Counts)
- 200 μ A ~ 10 A DC
- 600 V AC/DC
- Manual Ranging
- With holster & stand
- Continuity Test
- Transistor (hFE) test
- Data Hold



Economical & Fast Moving Product



SPECIFICATIONS

DC Voltage	Range	200 mV, 2 V, 20 V, 200 V, 600 V
	Basic Accuracy	\pm (0.5 % reading + 3 digits)
	Input impedance	1 M Ω
AC Voltage	Range	200 V, 600 V
	Basic Accuracy	\pm (2 % rdg + 10 digits)
	Freq. Response	50 ~ 500 Hz
DC Current	Range	200 μ A, 2 mA, 20 mA, 200 mA, 10 A
	Basic Accuracy	\pm (1.8 % rdg + 2 digits)
Resistance	Range	200 Ω , 2 K Ω , 20 K Ω , 200 K Ω , 2 M Ω
	Basic Accuracy	\pm (1% rdg + 10 digits)
Diode Test & Continuity Test		Provided
Transistor (hFE) Test		Provided
Data Hold Facility		Provided
Power Source		9 V (6F22)
Accessories Supplied		Test Leads, User Manual & Battery (Installed / Kept Aside)
Dimension & Weight		138 x 72 x 37 mm & Approx. 170 gms. (Including Battery)

* All Specifications & appearances are subject to change without prior notice

