


LP3443LT1G

20V P-Channel Enhancement-Mode MOSFET




1. FEATURES

- $V_{DS} = -20V$
- $R_{DS(ON)} \leq 70m\Omega, @V_{GS} = -4.5V, I_{DS} = -4.7A$
- $R_{DS(ON)} \leq 110m\Omega, @V_{GS} = -2.5V, I_{DS} = -1.0A$
- We declare that the material of product compliance with RoHS requirements and Halogen Free.
- ESD rating of class 0 (<100V)per Human Body Model.

2. APPLICATIONS

- Advanced trench process technology
- High density cell design for ultra low on-resistance



3. DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
LP3443LT1G	P34	3000/Tape&Reel
LP3443LT3G	P34	10000/Tape&Reel

4. MAXIMUM RATINGS($T_a = 25^\circ C$)

Parameter	Symbol	Limits	Unit
Drain–Source Voltage	V_{DS}	-20	V
Gate–to–Source Voltage – Continuous	V_{GS}	± 12	V
Drain Current			A
– Continuous $T_A = 25^\circ C$	I_D	-4.7	
– Pulsed (Note 1)	I_{DM}	-20	
Avalanche Current($L=0.1mH$)	I_{AS}	10	A
Avalanche Energy($L=0.1mH$)	E_{AS}	5	mJ

5. THERMAL CHARACTERISTICS

Parameter	Symbol	Limits	Unit
Power Dissipation	P_D	1.1	W
		0.7	W
Thermal Resistance, Junction–to–Ambient(Note 2)	$R_{\theta JA}$	110	$^\circ C/W$
Junction–to–Ambient(Note 3)	$R_{\theta JA}$	207	
Junction–to–Case	$R_{\theta JC}$	90	
Junction and Storage temperature	T_J, T_{stg}	$-55 \sim +150$	$^\circ C$





- 1.Repetitive Rating: Pulse width limited by the maximum junction temperature.
- 2.1-in² 2oz Cu PCB board.
- 3.Surface mounted on FR4 board using the minimum recommended pad size.

6. ELECTRICAL CHARACTERISTICS (Ta= 25°C)




Characteristic	Symbol	Min.	Typ.	Max.	Unit
STATIC					
Drain–Source Breakdown Voltage (VGS = 0, ID = -250μA)	VBRDSS	-20	-	-	V
Gate Threshold Voltage (VDS = VGS, ID = -250μA)	VGS(th)	-0.6	-0.85	-1.4	V
Zero Gate Voltage Drain Current (VGS = 0, VDS = -20 V)	IDSS	-	-	-1	μA
Gate-to–Source Leakage Current (VDS = 0 V, VGS = ±12 V)	IGSS	-	-	±100	nA
Static Drain–Source On–State Resistance(Note 4) (VGS = -4.5V, ID = -4.7A) (VGS = -2.7V, ID = -3.8A) (VGS = -2.5V, ID = -1.0A)	RDS(on)	- - -	58 63 75	70 90 110	mΩ
Diode Forward Voltage (VGS = 0 V, ISD = -1.7 A)	VSD	-	-	-1.2	V
DYNAMIC					
Total Gate Charge@10V	(VDS = -10V, ID = -1.5A)	Qg	-	20	nC
Total Gate Charge@4.5V		Qg	-	9	
Gate-to–Source Gate Charge		Qgs	-	1.5	
Gate-to–Drain Charge		Qgd	-	2.7	
Turn-On Delay Time	(VDD = -10V, RL = 10Ω, ID = -1A, VGEN = -4.5V, RG = 6.2Ω)	td(on)	-	18	ns
Rise Time		tr	-	25	
Turn-Off Delay Time		td(off)	-	88	
Fall Time		tf	-	42	
Input Capacitance	(f = 200kHz, VDS = -10 V)	Ciss	-	869	pF
Output Capacitance		Coss	-	82	
Reverse Transfer Capacitance		Crss	-	73	

4. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.



7. ELECTRICAL CHARACTERISTICS CURVES






7. ELECTRICAL CHARACTERISTICS CURVES(Con.)




7. ELECTRICAL CHARACTERISTICS CURVES(Con.)



8.OUTLINE AND DIMENSIONS



SECTION B-B




SOT23			
DIM	MIN	NOR	MAX
A	0.89	-	1.12
A1	0.01	-	0.10
A2	0.88	0.95	1.02
b	0.30	-	0.50
b1	0.30	0.40	0.45
c	0.08	-	0.20
c1	0.08	0.10	0.16
D	2.80	2.90	3.04
E	2.10	-	2.64
E1	1.20	1.30	1.40
e	0.95BSC		
e1	1.90BSC		
L	0.40	0.46	0.60
L1	0.54REF		
θ	0°	-	8°
All Dimensions in mm			

GENERAL NOTES

- 1.Top package surface finish $Ra0.4\pm0.2\mu m$
- 2.Bottom package surface finish $Ra0.7\pm0.2\mu m$
- 3.Side package surface finish $Ra0.4\pm0.2\mu m$

9.SOLDERING FOOTPRINT



SOT23	
DIM	(mm)
X	0.80
Y	0.90
A	2.00
B	0.95
C	0.95

DISCLAIMER

- Curve guarantee in the specification. The curve of test items with electric parameter is used as quality guarantee. The curve of test items without electric parameter is used as reference only.
- Before you use our Products for new Project, you are requested to carefully read this document and fully understand its contents. LRC shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any LRC's Products against warning, caution or note contained in this document.
- All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using LRC's Products, please confirm the latest information with a LRC sales representative.